

F25656

F25622

F27275


Grey Thermoplastic Rubber Caster

Thermoplastic rubber caster, rigid or swiveling, available with or without break



Advantages and benefits

- Smooth, non-marking rolling.
- Thermoplastic rubber designed to resist caustic chemicals, oils, and wear.
- Polypropylene hub won't dent, mar, stain or fade.
- Two hardened, polished ball bearings in independent rows roll freely in large-diameter lubricated tracks.
- Corrosion-resistant zinc finish.

Non-marking tread:



Hardwood

Tile / Linoleum / Ceramic

Conditions :

- *Water: Optimal*
- *Solvents: Optimal*
- *Detergents: Efficient*
- *Acids: Efficient*
- *Extreme cold : Efficient*
- *Extreme heat : Not recommended*
- *Petroleum products: Optimal*

Recommended surfaces:



Product number	Description	Wheel Diameter	Load Capacity	Tread Width	Overall Height
F25656	102mm Swiveling caster	102 mm (4")	112 kg (247 lbs)	32 mm (1-1/4")	126 mm (5")
F25622	102mm Swiveling caster w/break	102 mm (4")	112 kg (247 lbs)	32 mm (1-1/4")	126 mm (5")
F27275	102mm Rigid caster	102 mm (4")	112 kg (247 lbs)	32 mm (1-1/4")	126 mm (5")
F25657	127mm Swiveling caster	127mm (5")	135 kg (298 lbs)	32 mm (1-1/4")	156 mm (6-1/8")
F25371	127mm Swiveling caster w/break	127mm (5")	135 kg (298 lbs)	32 mm (1-1/4")	156 mm (6-1/8")
F27276	127mm Rigid caster	127mm (5")	135 kg (298 lbs)	32 mm (1-1/4")	156 mm (6-1/8")