

### Euro series rubber caster

F24802



F24797



F24791



Euro series rubber caster, rigid or swiveling, available with or without "FULL LOCK" break.



#### Advantages and benefits

- Metal thread guard.
- Corrosion-resistant zinc finish.
- "Full Lock" brake system locks the wheel and swivel for ease of use .
- Fully housed ball bearing eliminates the need to lubricate an axle, reducing maintenance costs.
- Double hardened ball bearings for quieter rolling

#### Recommended surfaces:



#### Conditions :

- *Water: Optimal*
- *Solvents: Not recommended*
- *Detergents: Efficient*
- *Acids: Not recommended*
- *Extreme cold: Not recommended*
- *Extreme heat : Not recommended*
- *Petroleum products : Efficient*

See next page for product list.

## Product list and technical information

### Recommended surfaces:



Product number	Description	Wheel Diameter	Load Capacity	Tread Width	Overall Height
F24790	80mm Swiveling caster	80mm (3-1/8")	50 kg (110lbs)	25mm (1")	105mm (4-1/8")
F24801	80mm, Swiveling caster w/"FULL LOCK" break	80mm (3-1/8")	50 kg (110lbs)	25mm (1")	105mm (4-1/8")
F24796	80mm Rigid caster	80mm (3-1/8")	50 kg (110lbs)	25mm (1")	105mm (4-1/8")
F24791	100mm Swiveling caster	100mm (4")	70 kg (154lbs)	30mm (1-3/16")	128mm (5-1/16")
F24802	100mm, Swiveling caster w/"FULL LOCK" break	100mm (4")	70 kg (154lbs)	30mm (1-3/16")	128mm (5-1/16")
F24797	100mm Rigid caster	100mm (4")	70 kg (154lbs)	30mm (1-3/16")	128mm (5-1/16")
F24792	125mm Swiveling caster	125mm (5")	100 kg (220lbs)	37mm (1-7/16")	155mm (6-1/8")
F24803	125mm, Swiveling caster w/"FULL LOCK" break	125mm (5")	100 kg (220lbs)	37mm (1-7/16")	155mm (6-1/8")
F24798	125mm Rigid caster	125mm (5")	100 kg (220lbs)	37mm (1-7/16")	155mm (6-1/8")
F24788	160mm Swiveling caster	160mm (6-5/16")	140 kg (309lbs)	40mm (1-9/16")	195mm (7-11/16")
F24794	160mm Rigid caster	160mm (6-5/16")	140 kg (309lbs)	40mm (1-9/16")	195mm (7-11/16")
F24793	200mm Swiveling caster	200mm (7-7/8")	205 kg (452lbs)	50mm (2")	235mm (9-1/4")
F24799	200mm Rigid caster	200mm (7-7/8")	205 kg (452lbs)	50mm (2")	235mm (9-1/4")